WEAR VOLUME 174, NUMBERS 1–2, MAY 1994

Contents

Instability in the tribochemical wear of silicon carbide in unlubricated sliding contacts 1
P. Andersson (Espoo, Finland) and A. Blomberg (Uppsala, Sweden)

Adhesion and adhesional friction at the contact between solids 9
S.K. Roy Chowdhury and P. Ghosh (Kharagpur, India)

Three-body abrasive wear of ceramic materials. 21
T. Yamamoto (Kanagawa, Japan), M. Olsson and S. Hogmark (Uppsala, Sweden)

Antiwear/extreme pressure performance of graphite and molybdenum disulfide combinations in lubricating greases 33
J.P. Antony, B.D. Mittal, K.P. Naithani, A.K. Misra and A.K. Bhatnagar (Faridabad, India)

Testing miniature, in particular polymer–polymer, journal bearings 39
Z. Rymuza, Z. Kusznierewicz and G. Mańturzyk (Warsaw, Poland)

Fretting wear of selected ceramics and cermets 47
P.Q. Campbell, J.P. Celis, J.R. Roos and O. Van Der Biest (Leuven, Belgium)

The behaviour of block-like residual austenite of 52100 steel in sliding wear 57
L. Hong, L. Jia-Jun and Z. Bao-Liang (Beijing, China)

The variation of hardness and wear coefficient in sliding wear of copper and aluminum alloys 63
M. El-Tayeb (Cairo, Egypt)

The influence of surface roughness and oil viscosity on the transition in mixed lubricated sliding steel contacts 71
S. Andersson and E. Salas-Russo (Stockholm, Sweden)

Microstructural effects on the sliding wear resistance of a cobalt-based alloy 81
A. Frenk and W. Kurz (Lausanne, Switzerland)

Additive–additive interactions: search for synergistic FM–EP–AW composition 93
R. Sarin, D.K. Tuli, A.S. Verma, M.M. Rai and A.K. Bhatnagar (Faridabad, India)

Wear properties of argon implanted poly(ether ether ketone). 103
G.R. Rao, E.H. Lee and L.K. Mansur (Oak Ridge, TN, USA)

The surface morphology and structure of carbon–carbon composites in high-energy sliding contact. 111
B.K. Yen and T. Ishihara (Yokohama, Japan)

Fade and wear characteristics of a glass-fiber-reinforced phenolic friction material. 119
P. Gopal, L.R. Dharani and F.D. Blum (Rolla, MO, USA)

Friction and wear of PAN/pitch-, PAN/CVI- and pitch/resin/CVI-based carbon/carbon composites 129
J.D. Chen and C.P. Ju (Tainan, Taiwan)

Thermoelastic evolution of contact area and mound temperatures in carbon graphite electrical brushes 137
C.-T. Lu and M.D. Bryant (Austin, TX, USA)

Cutting performance and wear mechanism of alumina-based ceramic tools when machining austempered ductile iron 147
M. Masuda, T. Sato, T. Kori (Tokushima, Japan) and Y. Chujo (Kagawa, Japan)

The role of porosity in the dry sliding wear of a sintered ferrous alloy 155
B. Dubrujeaud, M. Vardavoulias and M. Jeandin (Evry, France)

Reassessment of cryotribology theory 163
P.C. Michael, Y. Iwasa and E. Rabinowicz (Cambridge, MA, USA)

A method for optimizing the particle flux in erosion testing with a gas-blast apparatus 169
P.H. Shipway and I.M. Hutchings (Cambridge, UK)

The erosion–oxidation behavior of HVOF Cr_3C_2–NiCr cermet coating 177
B.Q. Wang and K. Luer (Richmond, VA, USA)

A model for the abrasive wear resistance of multiphase materials. 187
N. Axén and S. Jacobson (Uppsala, Sweden)

Elsevier Science S.A.

The improvement of three-body abrasive wear of plain carbon steel by thermochemical treatments 201
H.-J. Kim and Y.-G. Kweon (Pohang, Korea)

Thermal decomposition of dibenzyl disulphide and its load-carrying mechanism. 209
S. Płaza, B. Mazurkiewicz and R. Gruziński (Łódź, Poland)

Scanning electron microscopic studies of worn-out leaded aluminium–silicon alloy surfaces 217
A. Sharma and T.V. Rajan (Jaipur, India)

Short Communications

Surface damage of SiC(W)/SiC by abrasion and indentation. 229
D.F.W.Z.Y. Mao (Hangzhou, China)

Rise in fatigue strength of Ti by extremely mild abrasive processing 235
S. Watanabe, J. Amano and H. Furuichi (Matsue, Japan)

Wear mechanism of silicon carbide: new observations 239
J. Takadoum, Z. Zsiga and C. Roques-Carmes (Besançon, France)

Notes on Contributors 243

Author Index 247

Subject Index 249

The publisher encourages the submission of articles in electronic form thus saving time and avoiding rekeying errors. A leaflet describing our requirements is available from the publisher upon request.